

Specifications for OT Audio and Microphone System

Package B

S. N.	Particulars	Qty
I.	AUDIO SECTION	
1.	<u>Speakers for Audio System (4 Pieces)</u> <ul style="list-style-type: none"> • At least X10i10" Inch Driver Peak Power 1000 Watt Acoustical specifications Frequency Response(-3db):60Hz-20kHz Dispersion (H x V): 50-100° x 60° Nominal Impedance (Ohm):8Ω 	4 Pcs
2.	<u>Power Amplifier</u> <ul style="list-style-type: none"> • At least Two-channel, 850W with of 4Ω Power Amplifier 	1 Pc
3.	<u>Mixture Audio System</u> <ul style="list-style-type: none"> • At least 16-Input 2/2-Bus Premium Mixer with XENYX Mic Preamps and Compressors, Klark Teknik Multi-FX Processor, Wireless Option and USB/Audio Interface 	1 Pc
4.	<u>Handheld Microphones (2 Handheld)</u> <ul style="list-style-type: none"> • At Least of High-Performance 2.4 GHz Digital Wireless System with 2 Handheld Microphones and Receive 	2 Pcs
5.	<u>Microphone Pin Type with Receiver</u> <ul style="list-style-type: none"> • At least of 8-channel Wireless Belt-pack System with 1 unit Stationary Receiver and Belt-pack Transmitter – 2.4GHz. • At Least Mini 3 xlr Connection Low-Profile Microphone Frequency Response of 60 Hz to 15 kHz Built from Stainless Steel Bendable and Flexible Skin Color Blends to Avoid Distractions Lightweight at 0.25 oz Includes Windscreen Includes Cable Clip and Carrying Pouch 	1 set
6.	<u>Wall Mount for Speakers</u> <ul style="list-style-type: none"> • Heavy Duty for Wall Mount Speaker 	4 Pcs
7.	<u>3-pin Male XLR Connector with Nickel Finish and Silver Contacts</u>	4 Pcs
8.	<u>3-pin Female XLR Connector with Nickel Finish and Silver Contacts</u>	4 Pcs
9	<u>Professional Speaker Wire</u> <ul style="list-style-type: none"> • At least of cable 2.5 sq.mm. 2 core Multi-strand Speaker Cable 	1 Roll

